MIPS-12D

HE-12 Series Power Supply

MIPS-12D HE-12 Series Power Supply now with higher current capacity.

Powers any combination of HE Series modules when mounted in a MIRC-12V rack chassis.

CATV









Features

- Upgraded current capacity
- 27% higher on 5 VDC
- 11% higher on 12 VDC
- Fan cooled
- Wide AC input range

Ordering Information

Model Stock # Description

MIPS-12D 7722D HE-12 Series Power Supply

Rev. No. 110711

Specifications

INPUT

MIPS		
	Connectors:	IEC
	AC Voltage Range:	100 VAC to 240 VAC ± 10%
	ACFrequency:	50 to 60 Hz

OUTPUT

MIPS	<u> </u>				
Connectors 37 pin D 5 VDC @ 7.0A 12 VDC @ 4.5A		37 pin D 5 VDC @ 7.0A 12 VDC @ 4.5A			

General

Dimensions (W x D x H):	4.2 x 3.5 x 7.5 inches (106 x 89 x 190 mm)
Weight:	2.6 lbs (1.2 kg)
Operating Temperature:	32 to 122 °F (0 to 50 °C)
Storage Temperature:	-13 to 158 °F (-25 to 70 °C)
Operating Humidity:	0 to 95% RH @ 35 ℃ max, non-condensing
Storage Humidity:	0 to 95% RH @ 35 °C max, non-condensing

Alarms/Monitoring/Control

Truling, Wolffer g, Control				
Front Panel				
Power Indicator:	Green LED			



Related Products

Model Description

MIRC-12V HE Series vented rack chassis

Call Us: 954.427.5711
Toll Free: 888.293.5856