

AXE7800 Tri-Band Wi-Fi 6E Router

MODEL: EX920

Overview

EX920 is a high-performance Wi-Fi 6E Tri-band mesh wireless router with two 2.5Gbps Ethernet ports and one USB 3.0 port. Deliver even more faster Wi-Fi speeds with less interference and congestion while being backwards compatible with 802.11a/b/g/n/ac Wi-Fi devices. Perfect for FTTH deployment and a fully connected home.



AXE7800 Tri-Band Wi-Fi

Deliver total Wi-Fi speeds up to 7.8 Gbps across 6 GHz, 5 GHz, and 2.4 GHz bands for even faster speeds, lower latency, and better online experience.



Works on 6 GHz Band

Minimize congestion with greenfield spectrum to enable high-bandwidth applications that require faster data throughput.



2.5G Wired Connection

Take full use of the bandwidth speeds to 2.5 Gbps throgh a 2.5 GE WAN port and a 2.5 GE LAN port for even faster internet access and wired connection.



Easy Remote Management

TR-069 and TR-369 protocols, Aginet app, and TAUC (TP-Link Aginet Unified Cloud) are supported, service providers can manage multiple devices remotely.





Specifications

Hardware

• Interface

1× 10/100/1000/2500 Mbps RJ45 WAN Port, 1× 10/100/1000/2500 Mbps RJ45 LAN Port, 2× 10/100/1000 Mbps RJ45 LAN Ports, 1× USB 3.0 Port

• Antenna

Internal Wi-Fi antennas

• External Power Supply

12VDC/3.3A

• Dimensions (W * D * H)

4.5 × 4.5 × 9.1 in (115 × 115 × 232 mm)

Button

Power On/Off Button, Reset Button, Wi-Fi On/Off Button, WPS Button

• CPU

2 GHz ARM Quad-Core CPU

Wireless

- Wireless Standards IEEE 802.11ax 6GHz, IEEE 802.11a/n/ac/ax 5GHz, IEEE 802.11b/g/n/ax 2.4GHz
- Mesh Protocol
 802.11k/v/r
- Frequency 2.4GHz, 5GHz, and 6GHz
- Signal Rate

574 Mbps on 2.4GHz, 4804 Mbps on 5GHz, 2402 Mbps on 6GHz

• Transmit Power

CE: <20dBm (2.4GHz); <23dBm (5GHz); <23dBm (6GHz) FCC: <30dBm (2.4GHz); <30dBm (5GHz); <30dBm (6GHz)

- Wireless Security
 WPA/WPA2/WPA3 Personal, WPA2 Enterprise
- Wireless Function

Enable/Disable Wireless Radio, WMM, Wireless Statistics, Multi-SSID, Guest Network, TX Beamforming

Wireless Schedule

Supports 2.4 GHz, 5 GHz, and 6 GHz Wireless Schedule

• EasyMesh Support Seamless Roaming, Self-healing, 80211k/v/r Support

Software

- Working Mode
 - Router Mode, Access Point Mode
- WAN Type
 Dynamic IP/Static IP/PPPoE/PPTP/L2TP/Bridge
- Protocols
 - Supports IPv4 and IPv6
- Multi SSID

Up to 3 SSIDs for each band (including main SSID)

• Features

Parental Control, QoS (Quality of Service), Address Reservation, Port Forwarding, Cloud Firmware Upgrade, Firewall, Network Diagnostic, CWMP, Traffic Statistic, 1024-QAM, MU-MIMO, OFDMA, IPSEC VPN

• Management

Local management: WebGUI management, Aginet app management Remote management: TR-069, TR-181, TR-369, TR-111, TR-143 Cloud management: TAUC

DHCP

Server, DHCP Client List, Address Reservation

Port Forwarding

Virtual Server, Port Triggering, UPnP, DMZ

- Dynamic DNS
- NO-IP, DynDNS
- VPN Server
 PPTP. OpenVPN. IPSec
- VPN Pass-through
- IPSec, PPTP, L2TP
 Access Control

Parental Control, Local Management, Host List, White/Black List

• Firewall Security

DoS, SPI Firewall, IP and MAC Address Binding

Others

• System Requirements

Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1,10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browers or higher.

- Certifications
 FCC
- Environment

Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~60°C (-40°F ~140°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Package Contents

AXE7800 Tri-Band Wi-Fi 6E Router EX920

- 1× RJ45 Ethernet Cable
- 1× Power Adapter
- 1× Quick Installation Guide

