

# TG3452 | Touchstone® TG3452 Cable Voice Gateway



## DOCSIS® 3.1 Cable Voice Gateway with 802.11ac Wi-Fi & MoCA®2.0

- Supports RDK-B based router stack
- Allows custom designed setups to be applied to monitor the end user more efficiently with multiple provisioning methods (SNMP, configuration file, remote web GUI access, TFTP, and TR-069)
- Flexibility of configuration and control with multiple local and remote access levels (user, admin, etc.)
- Support for full 8 hours or 24 hours standby support with the same base unit

The Touchstone TG3452 is a DOCSIS 3.1 home telephony gateway supporting 2x192 MHz OFDM in the downstream and 2x96MHz OFDMA in the upstream along with 32x8 channel bonding for up to 2.5 Gbps of broadband data. It combines two FXS ports of carrier-grade VoIP, a 4-port gigabit router and a dual band 802.11n and 802.11ac Wave2 wireless access point with battery back-up into a single integrated device.

The TG3452 serves as the hub of service delivery in the subscriber's home; providing high-speed data, voice and IP video to wired and wireless connected devices. The device is optimized for providing Gigabit data services over DOCSIS 3.1 WAN.

## Product Classification

**Regional Availability** Latin America | North America

**Product Type** Cable voice gateway

## General Specifications

<b>Access Technology</b>	DOCSIS 3.1
<b>Channel Bonding</b>	2x2 OFDM/A   Up to 32x8 SC-QAM
<b>Ethernet Ports</b>	4 x GigE
<b>Interfaces</b>	2 lines, RJ14 ("Line 1/2"), RJ11 ("Line 2")   4x RJ45 (10/100/1000 Base-T)   'F' type connector
<b>MoCA</b>	MoCA 2.0
<b>RF Downstream Frequency Range</b>	108-1002 MHz
<b>RF Downstream Bonded Channels, quantity</b>	Up to 32 SCQAM or 2 OFDM
<b>RF Downstream Input Sensitivity Level</b>	-15 dBmV to 15 dBmV
<b>RF Downstream Data Rate</b>	Up to 5 Gb/s
<b>RF Upstream Frequency Range</b>	5-42 MHz or 5-85 MHz (switchable)
<b>RF Upstream Bonded Channels, quantity</b>	Up to 8 SCQAM or 2 OFDMA
<b>RF Upstream Output Level</b>	57 dBmV (64 QAM, 4-8 upstreams)   65 dBmV (16 QAM, single upstream)   65 dBmV (64 QAM, single upstream)
<b>RF Upstream Data Rate</b>	Up to 1 Gb/s



# TG3452 | Touchstone® TG3452 Cable Voice Gateway

---

<b>USB</b>	USB 3.1
<b>Voice</b>	Yes
<b>Voice Ports, quantity</b>	2
<b>Wi-Fi Interface Standard</b>	IEEE 802.11a/b/g/n/ac Wave2
<b>Wi-Fi Band</b>	2.4 GHz   5 GHz
<b>Wi-Fi Interface Standard at 2.4 GHz</b>	3x3, 802.11n
<b>Wi-Fi Interface Standard at 5 GHz</b>	4x4, 802.11ac

## Dimensions

<b>Height</b>	281.94 mm   11.1 in
<b>Width</b>	74.93 mm   2.95 in
<b>Length</b>	204.978 mm   8.07 in

## Electrical Specifications

<b>Input Voltage</b>	12 Vdc
----------------------	--------

## Environmental Specifications

<b>Operating Temperature</b>	0 °C to +40 °C (+32 °F to +104 °F)
------------------------------	------------------------------------

## Packaging and Weights

<b>Weight, net</b>	0.953 kg   2.1 lb
--------------------	-------------------

