## HT-580AXT

XGSPON Gateway AX10800 Tri-Band WiFi6E





Product Specifications





Wireless Standard Wireless Signal Rates 2.4GHz Band 5GHz Band 6GHz Band Operating Mode Wireless Communication Wireless Security Auto channel selection

Security SSID Broadcast Control Transmission speed EasyMesh Rel3

802.11 a/b/g/n/ac/ax Up to 10.8 Gbps 4x4 11ax up to 1.2 Gbps 4x4 11ax up to 4.8 Gbps 4x4 llax up to 4.8 Gbps Auto by default Enable WPA / WPA2 / WPA3 Supported Supported Band & Client steering Enabled Enabled Wireless Auto



Single SSID

Steering

#### **Network** Features.

**GPON Standard** PPPoE, DHCP, static IP

connectivity

NAT

WAN connectivity on

MultiRangePort Forwarding

Virtual server, special Application & DMZ host

DHCP Server UPnP, DDNS

MAC Address Cloning **IGMP Snoop** 

QoS Traffic Control (IP)

**DNS Relay** 

Café-style guest network

ITU-T G.984.4, G.988, G.9807.X

DHCP by default

Supported

Supported

Supported

Supported Supported

Supported

Supported

Supported Supported

Supported



#### **Smart** Led.

Red Blue

White

Green

Boot or network fail Ready to install Internet access Internet access without WiFi connectivity

Security Features.

NAT for basic firewall support Supported Packet filtering firewall Supported Password authentication to gateway Supported



# **System**

Configuration download / upload Supported Telnet / SSH Supported SNTP Supported Remote & Web management Supported Self-Healing Supported TR-069 / TR-181 Supported Echo mode (wireless switch schedule) Supported



### **Physical** Features.

PON Port, FXS, Ethernet, Power, Interface

12V 3.5A DC **Power Supply** 

Reset, Power On/Off, WPS, Button WiFI On/Off

78mm x 203mm x 245mm Dimension


0° C ~ 40° C Operating Temperature

10% ~ 90%, noncondensing Operating Humidity


-20° C ~ 70° C Storage Temperature

5% ~ 90%, noncondensing Storage Humidity

Interface. TIT HEIGHTS







Call Us: 954.427.5711 Toll Free: 888.293.5856