

Enabling the hyperconnected world



2629GN



2629GN FiberLAN Desktop GPON ONT

Next generation FiberLAN PoE ONT with voice FXS ports optimized for desktop and wall-mount installations using DZS leading-edge GPON technology.

Features & Benefits

- + Supports 2.5Gbps/1.25Gbps (Downstream/Upstream) with integrated GPON WAN interface
- + Eight gigabit multi-rate 10/100/1000M Ethernet interfaces
- + 802.3af, at, and bt PoE++ compliant
- + Up to 240W of PoE power per ONT
- + Two POTS interfaces compliant to SIP and MGPC telephony standards
- + Enterprise LAN features (802.1x, LLDP)
- + Fiber management tray option

The DZS 2629GN series GPON ONTs is the next generation of ONTs designed for Enterprise and Hospitality deployments requiring secure, Ethernet connectivity and voice or fax interfaces with a compact footprint. The 2629GN GPON ONTs provide customers with 8 x 10/100/1000BaseT LAN ports, all with PoE++ capability, allowing for convenient connections to IP phones, PTZ cameras, wireless access points, and remote switches. Configurable per-port PoE limits help direct power where it is needed. The 2629GN LAN ports can be separated into different services allowing the configuration of dedicated ports for IP video and data for one or more business work groups or departments. Unique VLANs may be configured per user to ensure full isolation of each department's data traffic.

The DZS 2629GN includes one SC/APC GPON interface, four 10/100/1000Base-T ports, all with PoE++ capability allowing for powered connections to IP devices, and two FXS RJ11 voice ports for phone or fax. Configurable per-port PoE limits up to 60W on any port and 240W per system. The 2629GN is powered by a nominal 48-56VDC source from a centralized power distribution system that may also provide battery backup.

Service Scenario

The FiberLAN GPON network consists of an Optical Line Termination (OLT) located in a central location, and a set of Enterprise grade Optical Network Terminals (ONTs). All Ethernet LAN ports can be separated into different services allowing the configuration of dedicated ports for IP video and data for one or more business work groups or departments. Unique VLANs may be configured per user to ensure full isolation of each department's data traffic.

With LLDP-MED support for voice VLAN advertisement, 802.1x authentication, and DZS Dynamic VLAN Mapping capability for handling complex sets of packet classification rules, operators can expertly manage traffic on each ONT LAN port to provide optimum customer experiences.

Key Service Attributes

- + FSAN ITU-T G.984 GPON Class B+ compliant
- + Eight 10/100/1000MBase-T Ethernet ports, RJ45 supporting 1Gbps symmetrical services
- + All ports 802.3af, at, and bt PoE++ compliant
- + Two voice ports, FXS interfaces compliant to ANSI or ETSI standards, SIP and MGCP
- + Support of Radius 802.1x, LLDP
- + IPTV multicast, IGMPv2 and IGMPv3 services
- + Any-port, Any-service data model
- + Traffic management including Q-in-Q tagging, 802.1Q VLANs, multiple subscriber VLANs, per-port rate limiting
- + 802.1p priority bits, DiffServ and priority queues based on services types.
- + OMCI and TR-069/TR-98 management
- + DZS Universal Service Provisioning (USP), ONT SNMP Client
- + Local Web UI, DZS CPE Manager feature set
- + +48 VDC power source, option for battery backup

FiberLAN Desktop PoE ONT 2629GN



Product Specifications

Hardware

+ Dimensions

Width: 10.3" (260mm)

Depth: 6.1" (155mm)

Height: 1.4" (35mm)

+Weight 0.77 LB (0.35 kg) +256GByte

Flash Memory +512GByte SDRAM

(DDR3) +GPON WAN Interface

+Capacity:2.5Gbps Down/1.25Gbps Up

Interfaces

+WAN: 1 SC/APC port, GPON

+LAN:8 ports 10/100/1000MBase-T Ethernet

(RJ45)

+Telephone: 2 ports 2-wire RJ11

+Power: 1 2-pin barrel connector, 1 2x4 8-pin

connector or

+LED Indicators

+Recessed RESET button

GPON

+Class B+ optics, 20km (12.4 miles), reach,

max split 64

+Maximum ODN Attenuation, +28.5 dB link

budget

+GPON Type B redundancy support

+G.985 xPON co-existence filter

+Transmitter, 1310nm, +0.5 to +5 dBm, DBF

+Receiver, 1490nm, -28 dBm, APD/TIA

+Forward Error Correction (FEC) per G.989.3

+Dying Gasp

Ethernet LAN ports

+Auto-MDI-X crossover control

+Auto-Speed or manual selection

+IEEE 802.3af, at, and bt PoE support on all

ports

+Max 61.6W PoE load on any port up to

123.2W total

+IEEE 802.3ab 1000Base-T

+IEEE 802.3u 100Base-T

+IEEE 802.3az EEE

+IEEE 802.1x Authentication

Telephone

+SIP (RFC 3261)

+ MGCP

+Codec: G.711 (u-law and A-law), G.729B,

G.726

+RENs per line: 5 maximum

+Drop length: Residential short loop, 152.4

m (500 ft.)

+Output max: 25mA

+Ring voltage: 48Vrms @ 20/25 Hz

Quality of Service

+HW-based internal IEEE 802.1p (CoS)

+Strict Priority (SP)

+802.1Q(VLAN tag) QoS mapping ToS/CoS

+8 queues per port

+Classified traffic can be tagged with VLAN

ID and Ethernet Priority bit, and can be

assigned to priority queues

+Classify packets into different IEEE 802.1p

priority queues according to DSCP values

(RFC 2475)

+The range of traffic shaping or rate-limit

shall between 64 Kbps to the maximum

port rate with 64kbps granularity. The

accuracy error shall be less than ±10%.

+DSCP IP CoS (RFC 2475)

Software Features

+IEEE802.1D and IEEE802.1Q

+Address learning with auto aging-L2/BPDU

Filter

+Support 2048 MAC learning addresses

+Multiple T-CONTs/GEM ports per device

+Flexible mapping between GEM port and

T-CONT

+Priority queues and scheduling on

upstream

+Activation with automatic discovered serial

Number and password

IP Routing and Firewall

+DHCP, Static-IP and PPPoE +

NAT/NAPT +DNS Proxy +DHCP

Server +UPnP, plug and play

IPv6

+IPv4 and IPv6 Dual-Stack-Lite

+Bridged Mode (transparent pass thru of IPv6

frames)

+IPv6 support of BRouted and PPPoE Bridged

VLANs

+DHCPv6 client and server

+Router Advertisement on LAN-side interfaces

+SLAAC for automatic acquisition of WAN-side

IPv6 addresses and GW

+CLI, HTTP and TR-069 management via IPv6

Environmental

+Operating Temperature 5~140°F (-15~+60°C)

Ex Temperature

+Storage temperature -40~121°F (-40~85°C)

+Operating humidity 5 to 95% (non-

condensing)

+Altitude: -200 to 10,000 feet (-61 to 3,048 m)

above sea level

Powering

+DC power, 44-56VDC

+Input power, 250W maximum (6W ONT TYP,

244W PoE)

+Power consumption, ~8W maximum

Management

+ITU-T 984.1/G988 compliant OMCI interface

+CPE Manager Web UI

+CLI over telnet

+SNMP Client

+TR-069, TR-104, TR-98

+DZS Universal Service Provisioning

+LED indications for status

Compliance

+FCC Part 15 Class B

+ICES-003 Class B

+EN55022, EN55024

+IEC 62368-1

+FDA IEC 60825-1

+RoHS 2015/863/EU



Ordering Information

Model	
2629GN	1x SC/APC port, GPON (Class B+) 8x 1G RJ45 ports, 802.3af, at, and bt PoE++ compliant 2x POTS RJ11 ports 1x 2-pin barrel connector 1x 8-pin barrel, 48VDC power input -15 to +60°C
HX-2629GN-00	No power supply