

# HT-360AXE

Active ETH Gateway  
AX5700 Dual Band WiFi6

HEIGHTS

AMT  
advanced media technologies®

## Access

2.5G Active ETH

## Plume HomePass

Home WiFi

Cyber

Parental

Speed checker

Home Management

## WiFi 6

2.4G 3X3

5G 4X4




# Product Specifications




## Wireless Features.

Wireless Standard	802.11 a/b/g/n/ac/ax
Wireless Signal Rates	Up to 5.7 Gbps
2.4GHz Band	3x3 Max up to 900 Mbps
5GHz Band	4x4 Max up to 4.8 Gbps
Operating Mode	Auto by default
Wireless Communication	Enable
Wireless Security	WPA / WPA2 / WPA3
Auto channel selection	Supported
Single SSID	Supported
Steering	Band & Client steering
Security	Enabled
SSID Broadcast Control	Enabled
Transmission speed	Wireless Auto



## Network Features.

Active ETH	2.5Gbps link speed
PPPoE, DHCP, static IP connectivity	WAN connectivity on DHCP by default
NAT	Supported
MultiRangePort Forwarding Virtual server, special Application & DMZ host	Supported
DHCP Server	Supported
UPnP, DDNS	Supported
MAC Address Cloning	Supported
IGMP Snoop	Supported
QoS Traffic Control (IP)	Supported
DNS Relay	Supported
Café-style guest network	Supported



## Smart Led.

Red	Boot or network fail
Blue	ready to install
White	Internet access
Green	Internet access without WiFi connectivity



## Security Features.

NAT for basic firewall support	Supported
Packet filtering firewall	Supported
Password authentication to gateway	Supported



## System Features.

Configuration download / upload	Supported
Telnet / SSH	Supported
SNTP	Supported
Remote & Web management	Supported
Self-Healing	Supported
TR-069 / TR-181	Supported
Echo mode (wireless switch schedule)	Supported



## Physical Features.

Interface	WAN, FXS, Ethernet, Power, USB 2.0, USB3.0
Power Supply	12V 2.5A DC
Button	Reset, Power On/Off
Dimension	200mm x 50mm x 255mm
Operating Temperature	0° C ~ 40° C
Operating Humidity	10% ~ 90%, noncondensing
Storage Temperature	-20° C ~ 70° C
Storage Humidity	5% ~ 90%, noncondensing

# Interface.



Reset to factory

Power ON/OFF

2x FXS

3x 1GE RJ45

2.5GE RJ45

2.5G AE

USB 3.0

USB 2.0

Power Jack