

NXG-BTCRYPT-S

SECURE AES-128 OUTPUT ENCRYPTION MODULE



KEY FEATURES

- » Standardized AES-128 encryption to quality content
- » Protects content to the viewing location
- » Compliant with Service Operator policies
- » Supports custom integration projects

PRODUCT OVERVIEW

The **NXG-BTCrypt-S** module creates a standardized AES-128 encryption to the output content for the NXG digital video platform. It encrypts single program MPEG-2 IP transport streams pulled off the NXG backplane. The **NXG-BTCrypt-S** supports the output of up to 256 SPTS channels per each front panel RJ45 GbE ports 1 & 2; ports 3 & 4 are reserved.

BT Labs' managed AES-128 output encryption module can be used to provide a secure IP connection to other vendor's networking equipment or to provide scrambled content all the way to viewing locations. The NXG-BTCrypt-S can support fixed, rotating, or custom key exchange.

ORDERING INFORMATION



MODEL	STOCK #	DESCRIPTION
NXG-BTCrypt-S	6776 S	Secure AES-128 Output Encryption Module

NXG-BTCRYPT-S

SPECIFICATIONS



INPUT

IP	2.5 Gb from NXG Mainframe Backplane
Video	MPEG-1, MPEG-2, H.264 (AVC/MPEG-4), H.265 (HEVC), Digicipher II
Audio	MPEG1, MPEG2, ADTS, AC3, E-AC3/AC3+

GENERAL

Dimensions (W x H x D)	1.15 x 7.0 x 15.5 in (29 x 178 x 394 mm)
Weight	2.0 lbs (0.9 kg)
Power	DC via NXG Mainframe Backplane
Power Consumption	11 W
Operating Temp.	32 to 122 °F (0 to 50 °C)
Storage Temp.	-13 to 158 °F (-25 to 70 °C)
Operating Humidity	0 to 95% RH @ 35 °C max, non-condensing

OUTPUT

IP	2x 1Gb RJ45 Ports (1 & 2)
TS Packet Length	All Formats Content Encrypted
Addressing	Multicast or Unicast
MPEG TS	SPTS

ALARMS & MONITORING

Front Panel	1x Status LED (Bicolor)
--------------------	-------------------------