

VIAVI

OneExpert CATV

A full-featured handheld for technicians at any skill level

OneExpert™ CATV helps field technicians fix problems right—the first time. A technician-friendly interface and OneCheck™ automated tests ease complex tasks with a simple dashboard that shows clear pass/fail results. And its future-proof modularity ensures years of use supporting CATV networks.

Comprehensive Tools Increase Productivity

We built expertise into OneExpert so that technicians at any skill level can quickly optimize performance. With a modular platform that adapts easily to rapidly changing technologies, OneExpert CATV is:

- Simple — Auto channel identification eliminates channel plan build, maintenance, and deployment overhead and enables automated testing without the potential for channel plan related test failures
- Fast — OneCheck uses powerful processing and exceptional speed to make more complete testing practical: a tech can run a comprehensive test, including MER and BER on all channels, in about a minute
- Powerful — More intelligent, powerful algorithms running in the background while testing enables the meter to point out any problems and suggest next troubleshooting steps



Benefits

- Simplifies and speeds testing and troubleshooting
- Improves compliance and audit performance
- Reduces rework
- Turns any technician into an expert

Features

- Real-time channel identification eliminates the need for channel plans and plan-related errors
- DOCSIS®, WiFi, Multi-Gigabit Ethernet capable, and TrueSpeed™ option
- Field-exchangeable DOCSIS/RF module
- A unique dual-diplexer design supports transition to extended return band
- WiFi, wireless personal area network, and StrataSync™ enabled
- Simultaneous ingress and downstream testing
- Optional fiber scope and power meter
- Optional ISDB-T Module

Applications

- Troubleshooting QAM carriers/home networks
- Verifying WiFi networks
- Testing Gigabit DOCSIS services
- Installing PON/RFoG including inspection, power levels, and RF performance
- Optional QAM video MPEG analysis for RPD activation
- Optional home leakage testing
- Network maintenance with forward and reverse sweep

Specifications

Frequency Range			Upstream Analysis — Port 2	
Automatically Switching Diplexer	Upstream	Downstream	Ingress spectrum scan	0.5 – 204 MHz
42/85	4-42 MHz and 4-85 MHz	54-1,004 MHz and 108-1,218 MHz	Sensitivity	-45 dBmV
42/204 MHz	4-42 MHz and 4-204 MHz	54-1,004 MHz and 258-1,218 MHz	RBW	300 kHz
65/204	4-65 MHz and 4-204 MHz	83-1,218 MHz and 258 MHz-1,218 MHz	Min detectable level upstream	-55 dBmV
85/204	4-85 MHz and 4-204 MHz	108-1,218 MHz and 258-1,218 MHz	Dynamic range	ONX-630 – 60dB; ONX-620 – 50dB
Accuracy	±10 ppm typical @25°C		Max total integrated power	55 dBmV, 4 – 10 MHz; 60 dBmV, 10 to 204 MHz
Downstream Analysis — Port 1			Accuracy	±2 dB typical at 25°C
AutoChannel plan builder	Auto detection of channel parameters (analog/digital, symbols, QAM)		Sampling rate	Hyper Spectrum™ FFT gapless technology - no missed samples, spans 0.5 -110 MHz, 110 to 160 MHz, and 160 to 204 MHz
Max input power	60 dBmV total integrated power		Return loss	>9.5 dB
Dynamic Range	>80 dB at 44 kHz RBW		Operation on powered tap	Operate with up to 90 V AC/DC on input port
Operation on powered tap	Operate with up to 90 V AC/DC on input port		Power detection/notification	Notify of AC/DC power presence on port 2 above 2 Volts
Power detection/notification	Notify of AC/DC power presence on port 2 above 2 Volts		Upstream Signal Generator	
Return loss	>9 dB		Number of signals generated simultaneously	From 1 to 8
			Signal types	signals either all CW or all modulated
			Modulation supported	QPSK, 16 QAM, and 64 QAM
			Symbol rates supported	5.12, 2.56, 1.28, 0.64, 0.32, and 0.16 Msym/s

Specifications Continued

Analog Channel Measurement		Hum Specification
Video and audio levels (dual)		
Standards	NTSC , PAL, SECAM	Hum frequency range
Min detectable signal	-50 dBmV (single channel)	25 Hz to 1000 Hz
Level accuracy	±1.5 dB from -20 dBmV to +50 dBmV typical at 25°C; ±2.0 dB, -10°C to +50°C	Minimum MER
RBW	300 kHz	Accuracy up to 5% hum
Carrier to Noise		From 5 to 10% +/- 1.0%
Channel types	NTSC , PAL, SECAM, non-scrambled	OFDM Signal Performance Metrics
Range	30 to 51 dB (NTSC, 4 MHz measurement bandwidth)	OFDM Channels
Required input level	0 to +40 dBmV with 77 analog channels present, maximum ±15 dB tilt 50 to 1,000 MHz	Level — max, min, average, standard deviation
Accuracy	±2.0 dB within specified measurement range ≤ 600 MHz	MER — max, min, average, standard deviation, percentile
Downstream Digital Channel Analysis		MER channel band graph
Calibrated power levels	-20 dBmV to +50 dBmV	Noise
Level accuracy	±1.5 dB from -20 dBmV to +50 dBmV typical at 25°C; ±2.0 dB, -10°C to +50°C	Echo
Modulation(s)	64, 128, and 256 QAM, OFDM	ICFR
Annex A: 5.057 to 6.952 MSPS		Spectrum/IUC
Annex B: 5.057 for 64 QAM and 5.361 MSPS for 256 QAM		in-carrier frequency response (dB)
Annex C: 5.274 MSPS for 64 QAM and 5.361 MSPS for 256 QAM		spectrum display, including carrier and ingress under carrier
Regional demods	DVB-C	OFDM Profile Analysis
Full span MER		Profiles A, B, C, D, NCP, and PLC (more profiles as implemented)
Ingress under carrier — full span ingress noise trace		Lock status, codeword errors <u>(corrected and uncorrected)</u>
Group delay and in-channel frequency response (ICFR)		DOCSIS Testing
Digital quality index (DQI) over time		Supports DOCSIS 3.1 bonding up to 32 SC-QAM + 2 OFDM downstream channels, 8 SC-QAM + 2 OFDMA upstream channels
Errored/severely errored seconds		Compliant with CableLabs® specifications for DOCSIS 3.1
Level, measured symbol rate, carrier frequency, modulation, interleaver depth		Compliant with CableLabs® specifications for DOCSIS 3.0 (32x8 bonding)

Specifications Continued

Displayed DOCSIS Results		MER			
Top level	Number of bonded channels, min receive level, max BER (pre-FEC), min and max MER, max transmit level, max ICFR (in-channel frequency response)	Specified range ¹ (with input level -5 to +20 dBmV)	21 to 40 dB, 64 QAM; 28 to 40 dB, 256 QAM; 16 to 44 dB OFDM		
Details	Downstream SC-QAM (over time charts: level, MER, BER, DQI), Upstream (charts: transmit over time, upstream ICFR, upstream EQ taps)	Max displayable range	50 dB		
Service tests	Registration, Throughput, Ping/Traceroute, Packet Quality; cable modem pass-through	Resolution	0.1 dB		
OFDM	OFDM selected in scan, number of subcarriers, PLC lock status, frequency, level, and MER, CWE (corr, uncorr); OFDM channel(s) - Level variation (max, min, avg), MER variation (max, min, avg), ICFR, profile analysis (locked, CWE corr, CWE uncorr)	Accuracy	±2 dB typical at 25°C		
Downstream		Minimum lock level	-15 dBmV		
Frequency range	54/85/108/258 to 1,000/1,218 MHz (dependent on currently active diplexer frequency)	BER — ChannelCheck and DOCSISCheck mode	Down to 1E-9 (pre and post FEC)		
Upstream		BER — OneCheck mode	Down to 1E-8 (pre and post FEC) default; 1E-9 user selectable		
OFDMA channels	≥2, per DOCSIS specification	Interleaver depth	128, 8 max		
Transmit level range (max)	+61 to +48 dBmV depending on modulation format and number of bonded carriers, per DOCSIS specification	Display/Interface/Usability			
SC-QAM channels	up to 8 per DOCSIS specification	High-brightness color LCD (800 x 480)	5 inch diagonal		
		Touch screen	Capacitive		
		Hard key navigation capable			
		Boot time	Approximately 20 sec		
Environmental					
For indoor/outdoor use	IP 54 light rain (0.5 in/hr; 1.27 cm/hr)				
Pollution	2°				
Drop	1 m (3.3 ft) onto concrete				
Temp range	Operating	-10 to 50°C (14 to 122°F)			
	Storage temp	-20 to 60°C (-4 to 140°F)			
Humidity	10 – 90% RH non-condensing				
RF immunity	8.5 V/m (for CATV measurements)				
Maximum altitude	4000 m (13,123 ft)				

¹MER range declines as input levels decrease. Expected MER range at MIN LOCK level of -15 dBmV.

Input/Outputs	
RF (2)	F connectors replaceable
Port 1	Downstream 54/85/108/258 MHz depending on diplexer
Port 2	Upstream 4 – 204 MHz and TDR
USB host (2)	
Ethernet (2)	RJ45 10/100/1000T
Power	Polarized
Remote Access/Connectivity	
VNC accessible via IP address	
HTTPS file access via IP address	
Mobile application via wireless personal area network	
Battery	
Field replaceable 96 W/hr 10.4 V, 10-cell LiIon	
Typical battery life	6 – 8 hr continuous, 15 – 20 hr typical usage
Battery charge time	4 Hrs (90%) 6 - 8 Hrs 100% (AC charger)
StrataSync Reporting	
Capability	
Session based (job/work order) file saving of results gathered at TAP, GB, and CPE	
Measurement screen capture save and recall	
StrataSync Core	Asset and data management
StrataSync Plus	Optional extended data management (6 years)
Weight	
ONX-620 & ONX-630	5.95 lb (2.7 kg)
Protective case and shoulder strap	0.95 lb
WiFi	
Test interface	802.11 a/b/g/n (2.4/5 GHz)
Tests	WiFi scan; WiFi access point (2.4 GHz only)
Scan results	SSID (secure set identification); Channel; Security setting; Power level; MAC address
Scan modes	AP list (access point); Channel graph; Time graph
Access point (IPX, TSX models only)	Configure OneExpert CATV as WiFi access point (Ethernet to WiFi bridge)

TrueSpeed Option	
Test Interface	Ethernet 10/100/1000, RJ45; Settings; Primary server; Fallback server; Profile with committed information rate (CIR) for upload and download
Measured and Calculated Results	Actual rate download/upload; Ideal rate download/upload; TCP efficiency; Round trip time (RTT); Maximum segment size (MSS)
Report Results	Committed information rate (CIR); Actual throughput; Target throughput; Saturation window; Target TCP throughput; Maximum segment size (MSS); Maximum transmit unit (MTU); Round trip time (RTT); Round trip time base; Maximum average throughput; Maximum peak throughput; Maximum window size; Window size per connection; Connections; Aggregate window; Actual throughput; Target throughput; Buffer delay; TCP efficiency; Total retransmits
Standards	VIAVI TrueSpeed VNF; RFC-6349
IP Video Option	
Test Interface	Ethernet 10/100/1000, RJ45
Modes	Terminate
Set-Top Box	IGMPv2 and v3 emulation client;
Emulation	RTSP emulation client
Service Selection	Broadcast auto; Broadcast MPEG2-TS/UDP; Broadcast MPEG2-TS/RTP/UDP; Broadcast RTP/UDP; Broadcast rolling stream; Broadcast TTS/UDP; Broadcast TTS/RTP/UDP; RTSP MPEG2-TS/(RTP)/UDP; RTSP MPEG2-TS/(RTP)/TCP; RTSP RTP/UDP; RTSP RTP/TCP

Video Settings	IPv4 IGMP version 2, 3; RTSP port; RTSP interoperability normal, Oracle, Siemens; IPv6 MLD version 2, 3
Video Source Address Selection	IP address and port number; IP address, port number, and VoD URL extension; RTSP port select; RTSP vendor select
Video Analysis Per Video Stream	Simultaneous stream support; 6 terminate; Number of active streams; Combined rate, current/max
QoS	Error indicator current/score; IGMP latency current/score; RTSP latency current/max/score; PCR jitter current/max/score/history; RTP packet jitter current/max/score/history; RTP lost current/max/score/history; Continuity error lost current/max/score/history; Overall current/max/score/history
Packet Loss Statistics	RTP loss distance errors current/max/total; RTP loss period errors current/max/total; Minimum RTP loss distance; Maximum RTP loss period; RTP packets lost count; RTP OOS count; RTP errors count; Continuity errors count; Ethernet RX errors, RX drops count
Video Stream Data Results (current/min/max/average)	Total, IP, Video, Audio, Data, Unknown
	Transport Stream Statistics
	Error indicator count; Continuity errors count; Sync errors count; PAT errors count; PMT errors count; PID timeouts count; Service name; Program name
	QoS Expert
	Compare two streams for error indicator, lost packets, jitter, latency
	PID Analysis (each stream)
	PID number; PID type (video, audio, data, unknown); PID description
	Layer Correlation
	Combined result view for Ethernet RX errors, RX dropped, video continuity error, video RTP lost, video loss distance total, video loss period total
	Standards
	RFC 2236, IGMP; RFC 2326, RTSP; ISO (IEC 13818), video transport stream and analysis; ETSI TR 10-290 V2.1, video measurements; TFC 1483, RFC-2684, ATM AAL5
	VoIP Software Option
	Test Interface
	Ethernet 10/100/1000, RJ45
	Supported Signaling Protocols
	SIP RFC 3621
	Supported Codec Configurations (ITU-T)
	G.711 u-law/A-law (PCM/64 kbps); G.722 64K; G.723.1 (ACELP/5.3, 6.3 kbps); G.726 (ADPCM/32 kbps); G.729a (GS-ACELP/8 kbps)
	VoIP Settings
	Auto-answer; Local alias; Outbound alias; Proxy gateway; Call control port; 100Rel support; SIP interoperability
	VoIP MOS
	Optimal measurement support

Specifications Continued

Fiber Test		Test Results
Optical Fiber Power Meter		Noise, ingress and frequency sweep test summary with pass/fail results; Mapped overview of coax network; Detailed view of cable lengths, faults, splitters, filters, amplifiers; Graphically depicts frequency sweep data
USB optical power meter	MP-60, MP-80	
Measurement units	dBm, mW, dB	
Connector input	Universal 2.5 and 1.25 mm connectors	
Power source	USB port	
Optical Fiber Scope		
USB optical fiber scope	P5000i	
Results for zone defects	Pass/fail	
Results for zone scratches	Pass/fail	
Low mag field-of-view (FOV)	Horizontal 740 µm, vertical 550 µm	
High mag field-of-view (FOV)	Horizontal 370 µm, vertical 275 µm	
Particle size detection	<1 µm	
Power source	USB port	
Setting for profile, tip, focus meter, button action		
Actions for live mode, test mode, high magnification		
Probe model, serial, firmware		
Home Network Test SmartID - Coaxial Cable Testing		
Test Interface	Coax using SmartID or SmartID Plus; Test Probes (near end): SmartID, SmartID Plus; Settings: Supports any cable coax type with configurable velocity of propagation (VOP) and cable compensation	
Tests	Locate cable runs with active RFIDs (requires SmartID Plus). Single-ended coax map (SECM)	
Tests Using SmartIDs as Remote Probes	Locate cable runs with SmartIDs; Dual-ended coax map (DECM)	
Standard Accessories		
Protective case with hand strap and detachable shoulder strap		
AC power supply with choice of country-specific adaptor plug		
Quick start guide		
StrataSync Core support		
ISDB-T Module	Specifications	
Frquency Range	130-767 MHz	
Resolution	0.1 MHz	
Channel Bandwidth	6 MHz	
ISDB-T Measurements		
Modulation type	DQPSK, QPSK, 16 QAM	
TMCC	64QAM(Auto Detection) TMCC	
Parameters	parameters: Mode, GI, Layers (Auto Detection)	
Lock Range	45 to +110 dBuV (total integrated power)	
MER Range	33dB	
MER Accuracy	+/- 2dB typical @ 25C ²	
BER	Pre-RS BER range ³ : 1E-2~1E-9 Post-RS BER: Pass/fail	
Constellation		
Channel Parameters identified	Modulation, GI, Segments, CCR, Mode, Interleaver	
User Selection	Channel Center Frequency Layer A, B, or C	

Description		Part Number	Description	Part Number
ONX-620 Packages				
Dual Diplexer			Seeker Home Leakage Test Kit	TRI-LKG-HL-METER-KIT
Basic	42/85	ONX-620D31-4285-1010-BAS	Home Leakage Software Option	ONX-CATV-SW-HL-LKG
	65/204	ONX-620D31-6520-1212-BAS	OneExpert CATV QAM Video MPEG verification option	ONX-CATV-SW-QAM-VIDEO
IPX	42/85	ONX-620D31-4285-1010-IPX	Return Path SNR Option	ONX-CATV-SW-RP-SNR-OCE
	65/204	ONX-620D31-6520-1212-IPX	Rapid Reverse Sweep Option*	ONX-CATV-RAPIDREVSW
	42/204	ONX-620D31-4220-1012-IPX		
	85/204	ONX-620D31-8520-1212-IPX		
TSX	42/85	ONX-620D31-4285-1010-TSX		
	65/204	ONX-620D31-6520-1212-TSX		
	42/204	ONX-620D31-4220-1012-TSX		
	85/204	ONX-620D31-8520-1212-TSX		
ONX-630 Packages				
NTX	42/85	ONX-630D31-4285-1012-NTX	ONX-630 42/204 MHz Sweep Ready Upgrade module	UPG-ONX-D31-S-4220-1012
	65/204	ONX-630D31-6520-1212-NTX	ONX-620 42/204 MHz Upgrade Module	UPG-ONX-D31-4220-1012
	42/204	ONX-630D31-4220-1012-NTX	ONX-620/630 85/204 MHz Upgrade Module	UPG-ONX-D31-S-8520-1212 (RF module only; requires trade-in)
SWX	42/85	ONX-630D31-4285-1012-SWX	Field Upgrade (via StrataSync) QAM Video option	UPG-ONX-CATV-SW-QAMVIDEO
	65/204	ONX-630D31-6520-1212-SWX	Field Upgrade (via StrataSync) Return Path SNR option	UPG-ONX-CATV-SW-RP-SNR
	42/204	ONX-630D31-4220-1012-SWX		
	85/204	ONX-630D31-8520-1212-SWX		
Options				
TrueSpeed	ONX-TRUE SPEED			
IP video	ONX-CATV-IPVIDEO			
DOCSIS 3.1	ONX-CATV-SW-D31			
VoIP	ONX-VOIP			
Forward Sweep	ONX-CATV-SW-FWD-SWEEP			
Reverse Sweep	ONX-CATV-SW-REV-SWEEP			
Reverse Sweepless Sweep	ONX-CATV-SW-REVSPLSSWP			
Reverse alignment	ONX-CATV-SW-REV-ALIGN			
Ingress expert	ONX-CATV-SW-INGRESS-EXP			
Return signal generator	ONX-CATV-SW-RSG			
Return signal generator w/ loop-back	ONX-CATV-SW-RSG-LOOP			
HomeTDR	ONX-CATV-SW-HOMETDR			

*Included on SWX models



Ordering Information continued

Description	Part Number
Bronze and Silver Warranty Extensions	
Five-year warranty	BRONZE-5
One calibration	SILVER-3
Five-year warranty and two calibrations	SILVER-5
Optional Accessories	
Replacement Charger (no power cord)	AC-CHARGER
Car Charger	AC-CAR-CHARGER
Replacement Fitted Case	ONX-CATV-STD-ACCY-KIT
Strand Hook	1019-00-1366
Replacement 96 W/Hr Battery	ONX-CATV-BATT-96WHR
Replacement screen protector (5 pack)	ONX-SCREEN-PROTECTION
Large accessory bag, fitted case, 12V adapter, strand hook, Ethernet patch cord (1 m), extra hand strap	ONX-CATV-DLX-ACCY-KIT
MP-80 USB optical power meter	MP-80A
MP-60 USB optical power meter	MP-60A
FI-60 live fiber identifier	FI-60
P5000i USB fiber scope	FBP-P5000I

Feature Matrix

		ONX-620		ONX-630		
		ONX Feature Bundle				
Feature		Basic	IPX	TSX	NTX	SWX
OneCheck	Dashboard with ingress scan, downstream summary, DOCSIS summary, and Session Expert summary	■	■	■	■	■
OneCheck details screens	Ingress scan — full graphic view	■	■	■	■	■
OneCheck downstream details	Full scan with channel details — level, hum, MER, BER, C/N, Echo, GD, ICFR	■	■	■	■	■
	System view (max dB delta, max video delta)	■	■	■	■	■
	Favorites	■	■	■	■	■
	Tilt	■	■	■	■	■
	Smart scan			■	■	■
	MER graph — all channels			■	■	■
	BER graph — all channels			■	■	■
	Off-air ingress detection (downsteam ingress under carrier)	■	■	■	■	■
OneCheck DOCSIS details	Downstream DOCSIS channel scan with channel details — level, MER, BER, C/N, echo, GD, ICFR	■	■	■	■	■
	Upstream DOCSIS channel scan with channel details — TX level, modulation type, ICFR		■	■	■	■
	DOCSIS throughput		■	■	■	■
	DOCSIS packet quality		■	■	■	■
OneCheck — Session Expert details	Problems detected table	■	■	■	■	■
	Suggested actions table	■	■	■	■	■
	Ingress comparison between TAP and GB	■	■	■	■	■
	Drop analysis between TAP and GB	■	■	■	■	■
	Detailed downstream comparison between TAP, GB, and CPE	■	■	■	■	■
	Detailed SmartScan comparison between TAP, GB, and CPE			■	■	■
	Detailed Off-air ingress comparison between TAP, GB and CPE	■	■	■	■	■
	Detailed DOCSIS comparison between TAP, GB, and CPE	■	■	■	■	■
	Detailed DOCSIS service test comparison between TAP, GB, and CPE		■	■	■	■

Feature Matrix

Feature	ONX-620		ONX-630		
	ONX Feature Bundle				
	Basic	IPX	TSX	NTX	SWX
ChannelCheck	Full scan with channel details — level, hum, MER, BER, C/N, Echo, GD, ICFR	■	■	■	■
	DS Spectrum w/ Ingress under the carrier (7-channels wide)	■	■	■	■
	System view (max dB delta, max video delta)	■	■	■	■
	Favorites graph (up to 16 Ch)	■	■	■	■
	Tilt	■	■	■	■
	DQI over time	■	■	■	■
	Level over time			■	■
	MER over time			■	■
	BER over time			■	■
	Downstream in-channel response graph			■	■
DOCSIS 3.1 testing	SmartScan™			■	■
	Constellation	■	■	■	■
	OFDM signal detection and identification in scan - automatic	Optional	Optional	Optional	■
	OFDM signal measurement	Optional	Optional	Optional	■
	OFDM signal MER throughout channel band over time	Optional	Optional	Optional	■
	OFDM signal level variation	Optional	Optional	Optional	■
	OFDM ingress under carrier analysis	Optional	Optional	Optional	■
	PLC detection, lock status, level, MER, CWE	Optional	Optional	Optional	■
	NCP lock status, CWE	Optional	Optional	Optional	■
	Profile analysis - lock status, CWE	Optional	Optional	Optional	■

Feature Matrix

Feature	ONX Feature Bundle				
	ONX-620 ONX-630				
	Basic	IPX	TSX	NTX	SWX
DOCSISCheck	Downstream DOCSIS channel scan with channel details — level, MER, BER, C/N, echo, GD, ICFR	■	■	■	■
	DQI over time	■	■	■	■
	Level over time			■	■
	MER over time			■	■
	BER over time with ES/SES			■	■
	Downstream in-channel response graph			■	■
	Upstream DOCSIS channel scan with channel details — TX level, modulation type, ICFR	■	■	■	■
	Transmit over time	■	■	■	■
	DOCSIS upstream in-channel frequency response graph			■	■
	Speed Check – throughput		■	■	■
	Packet quality — packet loss, round trip delay, jitter		■	■	■
	Ping/trace route		■	■	■
Ethernet testing	Pass through modem RJ-45 port		■	■	■
	Ethernet		■	■	■
	OneCheck Ethernet		■	■	■
	Speed Check - throughput		■	■	■
	Ping/Trace route		■	■	■
	FTP/HTTP upload/download		■	■	■
	Web browser	■	■	■	■
	VoIP SIP		■	■	■
	VoIP MOS		Optional	Optional	Optional
	IP video		Optional	Optional	Optional
WiFi testing	TrueSpeed™		Optional	Optional	Optional
	Ethernet		■	■	
	Ping		■	■	
	TrueSpeed		Optional	Optional	
	WiFi - 2.4GHz and 5GHz	SSID survey - graphical and tabular	■	■	■
	SSID levels over time		■	■	■
	Local WiFi access point		■	■	■

Feature Matrix

		ONX-620		ONX-630		
		ONX Feature Bundle				
Feature		Basic	IPX	TSX	NTX	SWX
Expert modes	Test point templates, custom limit plans and live/stored measurement comparisons				■	■
	Channel Expert				■	■
	DOCSIS Expert				■	■
	Ingress Expert	Optional	Optional	Optional	■	■
	Quick Check Expert	Optional	Optional	Optional	■	■
Return signal generator	Transmit up to 8 CW or QAM signals	Optional	Optional	Optional	■	■
Return signal generator with loopback	Transmit and receive up to 8 CW or QAM signals with simultaneous power level measurements	Optional	Optional	Optional	■	■
Sweep testing	Sweepless Sweep™				■	■
	Forward Sweep				Optional	■
	Reverse Sweep				Optional	■
	Reverse Sweepless Sweep™				Optional	Optional
	Reverse Alignment				Optional	■
Mobile app integration		■	■	■	■	■
Wireless personal area network		■	■	■	■	■
SmartID support	SmartID and SmartID Plus	■	■	■	■	■
WiFi Advisor support	WFED-300AC; SmartChannel Wizard	■	■	■	■	■
Optical fiber scope support — P5000i		■	■	■	■	■
Optical power meter support — MP-60, MP-80, FI-60 Fiber identifier		■	■	■	■	■
HomeTDR		Optional	Optional	Optional	Optional	Optional
Home Leakage Test		Optional	Optional	Optional	Optional	Optional
QAM Video MPEG verification					Optional	Optional
Return Path SNR		Optional	Optional	Optional	Optional	Optional
Rapid Reverse Sweep					Optional	■

*DOCSIS is a trademark of CableLabs.